

S690QL - SHAPED OFFCUT SPECIALS LIST (OUTSIDE)

		O/C SQ SIZE							
Sheet Name	Material	Thick	Length	Width	Qty	Theoretical Mass Usuable	Square Mass	Percentage Usable	Rate per Kg Exc Sandblast
B13-P10-S690QL-10MM	S690QL	10	1310	370	1	37	38	97%	R13.00
B7-P10-S690QL-10MM	S690QL	10	3030	610	1	83	145	57%	R13.00
B5-P12-S690QL-10MM	S690QL	10	1190	290	1	22	27	80%	R13.00
B5-P23-S690QL-10MM	S690QL	10	700	550	1	22	30	73%	R13.00
B7-P12-S690QL-10MM	S690QL	10	2300	480	1	54	87	62%	R13.00
B4-P28-S690QL-10MM	S690QL	10	900	900	1	50	64	79%	R13.00
B2-P30-S690QL-10MM	S690QL	10	1200	550	1	52	52	100%	R13.00
B2-P31-S690QL-10MM	S690QL	10	1200	550	1	52	52	100%	R13.00
B4-P24-10MM-S690QL	S690QL	10	820	625	1	40	40	100%	R13.00
B1-P4-S690QL-12MM	S690QL	12	2410	2025	1	228	460	50%	R13.00
B1-P17-S690QL-12MM	S690QL	12	1225	600	1	68	69	98%	R13.00
B7-P9-S690QL-12MM	S690QL	12	3550	250	1	31	84	38%	R13.00
B9-P16-S690QL-12MM	S690QL	12	1160	120	1	13	13	100%	R13.00
B13-P17-S690QL-16MM	S690QL	16	720	150	1	14	14	100%	R13.00
B9-P19-S690QL-16MM	S690QL	16	630	148	1	10	12	83%	R13.00
B8-P4-S690QL-20MM	S690QL	20	1825	365	1	105	105	100%	R13.00
B11-P6-S690QL-20MM	S690QL	20	2525	1215	1	176	482	36%	R13.00
B9-P28-S690QL-20MM	S690QL	20	2180	120	1	41	41	100%	R13.00
B12-P3-S690QL-20MM	S690QL	20	950	1110	1	97	166	59%	R13.00
B9-P18-20MM-S690QL	S690QL	20	1440	210	1	29	47	61%	R13.00
B1-P20-20MM-S690QL	S690QL	20	1825	365	1	105	105	100%	R13.00
B11-P10-35MM-S690QL	S690QL	35	1500	1099	1	172	453	38%	R13.00
B9-P26-S690QL-40MM	S690QL	40	1425	150	1	67	67	100%	R13.00